



TRI NUCLEAR CORP.

UF-600 Underwater Filter

Tri Nuclear has developed a large stand-alone underwater filter which is ideal for process large amounts of water rapidly for water clarity.

Tri Nuclear's underwater filters can be operated for long durations practically unattended without the need for maintenance or element change out, all while controlling water clarity and reducing dose rates.

Because the portable underwater filter is submerged, it needs no external shielding, or hoses running in or out of the water that may cause rippling, poor visibility or personnel exposure/contamination.

Tri Nuclear's underwater filters operate under negative pressure which allows the pump to be gravity seated and does not require any special tooling to install or remove the pump underwater.



UF-600 Housing and Pump

Features:

- Rapid system deployment via camlock hose connections, twist lock electrical connections, and control box upgrades
- All stainless steel construction
- Underwater service requiring no additional shielding
- Specialized tooling for rapid remote filter change out underwater

Specifications:

- | | |
|----------------------------|-----------------|
| • System Flow Rate: | 600 GPM |
| • No of Filters: | 4 Cartridges |
| • Hoses: | 2 Discharge |
| • Footprint: | 24" x 30" |
| • Height: | 99" |
| • Pump Weight: | 210 lbs. |
| • Housing Empty with Pump: | 460 lbs. |
| • Housing Full with Pump: | 965 lbs. |

Filter Cartridge Design:

Tri Nuclear's Filter Cartridges have pleated paper construction which provides a large filter area and long run times. Inside loading means that solids are trapped in the element and won't flake or slough off during change out.

"Operating" vs. "Complete" System

Each of the UF/UFV systems is sold in both the "Operating" and "Complete" system kits. The "Operating" system comes with only the basic components required to operate the system. The "Complete" system comes with the basic components and all accessory tooling.